

Commonwealth of Kentucky
Division for Air Quality
PERMIT STATEMENT OF BASIS

TITLE V DRAFT PERMIT NO. V-06-012

THE HON COMPANY

931 WING AVENUE, OWENSBORO KY.

JUNE 28, 2006

SAJJAD QUABILI, REVIEWER

SOURCE I.D. #: 021-059-00035

SOURCE A.I. #: 964

ACTIVITY #: APE20060001

SOURCE DESCRIPTION:

The HON Company operates a wood furniture manufacturing plant in Owensboro, Kentucky. The source is major for VOC and HAP emissions. The source applied to the Division to renew their Title V permit. They also applied to construct two additional paint spray booths in their production line to meet their projected customer demands. Each spray booth will comprise of six applicators.

PERMITTING BACKGROUND:

The HON Company is holding a Title V/Synthetic Minor permit. The current permit allows the source to operate five spray booths. In addition to the renewal of the permit, the source has requested an authorization to begin construction of two additional paint spray booths in their production line. VOC synthetic minor limit will remain unchanged to 225 tons per year in the renewed permit.

APPLICABLE REGULATIONS:

The HON Company is subject to the following regulations for their wood furniture manufacturing operations:

- A. 40 CFR 63 Subpart JJ, National Emission Standards for Wood Furniture Manufacturing Operations, applicable to an affected facility that is engaged, either in part or in whole, in the manufacture of wood furniture components and that is located at a plant site that is a major source as defined in 40 CFR part 63.2. Emission points EP 04, EP 05, EP 06, EP 07 and EP 08 are classified as existing source. EP 09 and EP 10 are classified as new source.
- B. 401 KAR 61:020, Existing process Operations, applicable to each affected facility or source, associated with a process operation, which is not subject to another emission standard with respect to particulate, commenced before July 2, 1975.
- C. 401KAR 50:012 Section 1(2) General Application of Administrative Regulations and Standards. In the absence of a standard specified in 401 KAR 50 to 65, administrative regulations, all major air contaminant sources shall as a minimum apply control procedures that are reasonable, available, and practical.
- D. 401 KAR 59:010, New Process Operations, applicable to each affected facility or source, associated with process operation, which is not subject to another emission standard with respect to particulate, commenced on or after July 2, 1975.

- E. Regulation 401 KAR 59:015, New indirect heat exchangers, applicable to an emission unit that has heat input capacity of more than one (1) million Btu/hr commenced on or after April 9, 1972.
- F. 40 CFR 60 Subpart Dc, Standards of performance for small industrial-commercial-institutional steam generating units, applies to HON's waste wood fired industrial boiler commenced after June 9, 1989 that has a maximum design heat input capacity between 10 mmBtu/hr and 100 mmBtu/hr. No records or reports are required for a wood fired industrial boiler with an input capacity less than 30 mmBtu/hr.
- G. 40 CFR 63 Subpart DDDDD; National Emission Standards for Hazardous Air Pollutants for Industrial, Commercial, and Institutional Boilers and Process Heaters is applicable to waste wood fired boiler (EP 01). The compliance date for this Subpart is September 13, 2007.

Compliance requirements for 40 CFR 63 Subpart DDDDD:

General Compliance:

- a. A site specific fuel analysis plan shall be developed according to §63.7521(b).
- b. Emission rate shall be calculated according to §63.7530(d). If the calculated emission rate is below the applicable limit, Hon shall demonstrate compliance with the applicable limit using fuel analysis. ***Otherwise, HON must demonstrate compliance through performance testing (§63.7505(c)).***

Initial Compliance:

- a. A site-specific fuel analysis plan shall be submitted 60 days before they intend to demonstrate compliance.
- b. HON shall demonstrate that calculated maximum emission rate (based on fuel pollutant content) is below emission limit.

Continuous Compliance:

- a. Annual performance test is not required.
- b. TSM, Cl, Hg fuel content shall be maintained below the limit established during the initial fuel analysis.
- c. The metals, Cl, Hg content of fuel shall be recalculated if HON plan to burn a new fuel.
- d. The metals, Cl, Hg content of each type of fuel shall be recalculated every 5 years.

COMPLIANCE ASSURANCE MONITORING (CAM):

The requirement for compliance assurance monitoring (40 CFR 64) is applicable to major sources that use pollution control systems to achieve regulatory or permit limits. The HON Company has no pollution control systems that are used for this purpose.

PERIODIC MONITORING:

The Division is requiring The HON Company to keep daily records of usage of sealers, coatings, adhesives and thinners at each of the spraying booths and to summarize those records at the end of each month. The source shall also keep records of the monthly and twelve months rolling total for VOC emissions at the plant.

MODELING:

The Division has performed Screen 3 modeling analysis for potential to emit toxic materials. Maximum annual concentrations of all concerned toxic substances were found less than the Prioritized Chronic Dose-Response Values for Screening Risk Assessments.

CREDIBLE EVIDENCE:

This permit contains provisions which require that specific test methods, monitoring or recordkeeping be used as a demonstration of compliance with permit limits. On February 24, 1997, the U.S. EPA promulgated revisions to the following federal regulations: 40 CFR Part 51, Sec. 51.212; 40 CFR Part 52, Sec. 52.12; 40 CFR Part 52, Sec. 52.30; 40 CFR Part 60, Sec. 60.11 and 40 CFR Part 61, Sec. 61.12, that allow the use of credible evidence to establish compliance with applicable requirements. At the issuance of this permit, Kentucky has only adopted the provisions of 40 CFR Part 60, Sec. 60.11 and 40 CFR Part 61, Sec. 61.12 into its air quality regulations.